

Claims

- [c1] What is claimed is:
- 1.A method for recovering an absolute time in pre-groove (ATIP) clock and an ATIP signal from a wobble signal through a reference clock, the ATIP clock being synchronized with the ATIP signal and the reference clock comprising a plurality of reference periods, each of the reference periods having a fixed interval, The method comprising:
- counting a number of reference periods of the reference clock occurring within a period of the wobble signal and generating a corresponding counting result;
- generating an average number according to a long-term average of the counting results;
- generating a wobble clock according to the average number and the reference clock;
- generating the ATIP signal according to the average number and the counting result; and
- generating the ATIP clock according to the ATIP signal and the wobble clock.
- [c2] 2.The method of claim 1 wherein the wobble clock is generated by dividing the reference clock by the average number.
- [c3] 3.The method of claim 1 wherein when generating the ATIP signal, a comparing result is first generated by comparing the counting result and the average number, and the ATIP signal is then generated by shaping a waveform of the comparing result through the wobble clock.
- [c4] 4.The method of claim 3 wherein the ATIP signal comprises a first signal and a second signal, a duration of the first signal corresponds to an interval of the wobble signal in which a number of reference periods is more than the average number, and a duration of the second signal corresponds to an interval of the wobble signal which has reference periods less than the average number.
- [c5] 5.The method of claim 4 wherein the ATIP clock is generated according to a synchronization between the ATIP signal and the wobble signal.
- [c6] 6.A circuit for generating a wobble clock through a reference clock and a

wobble signal, the reference clock comprising a plurality of reference periods, each of the reference periods having a fixed interval, the circuit comprising: a counter for counting the wobble signal according to the reference clock; a digital average processor connected to the counter for averaging an output of the counter to generate an average number; and a divider for dividing the reference clock by the average number so as to generate the wobble clock.

[c7] 7.The circuit of claim 6 further comprising a comparator for comparing the output of the counter with the average number so as to generate an ATIP signal.

[c8] 8.The circuit of claim 7 wherein the ATIP signal comprises a first signal and a second signal, a duration of the first signal corresponds to an interval of the wobble signal in which a number of reference periods is more than the average number, and a duration of the second signal corresponds to an interval of the wobble signal which has reference periods less than the average number.

[c9] 9.The circuit of claim 7 further comprising a waveform shaping processor connected to the divider and the comparator for synchronizing the ATIP signal with the wobble signal.

[c10] 10.The circuit of claim 6 further comprising a synchronization circuit for generating an ATIP clock synchronized with the ATIP signal through triggers of the wobble clock.

[c11] 11.The circuit of claim 10 wherein the synchronization circuit further comprises a status generator for generating a status signal according to a voltage level of the ATIP signal when triggered by the wobble signal; when the ATIP signal changes the voltage level, the status signal changes its status according to the ATIP signal when triggered by the wobble signal.

[c12] 12.The circuit of claim 11 wherein the synchronization circuit further comprises a period counter for counting a number of periods occurring within a period of the wobble signal according to the status signal so as to generate the ATIP clock.